


TARAFLEX™运动多功能3.8 TARAFLEX™ MULTI-USE 3.8

描述 Description	标准 Standard	要求 Requirement	单位 Unit	TARAFLEX™ MULTI-USE 3.8
Product Description 规格				
Total thickness 总厚度	EN 428	-	mm	3.8
Weight 重量	EN 430	-	kg/m ²	1.9
Width of sheet 卷宽	EN 426	-	lm	1.5
Length of sheet 卷长	EN 426	-	lm	30 Max
Sport Characteristics 运动特性				
Shock absorption 震动吸收	EN 14808	≥25	%	21
	DIN 18032	-	%	24
Vertical deformation 垂直变化值	EN 14809	≤3.5	mm	≤3.5
Energy return 能量返还	NF P 90 203	≥0.31	m/s	≥0.31
Sliding coefficient 滑动系数	EN 13036-4	80 - 110	-	80 - 110
	DIN 18032	0.4 - 0.6	-	0.4 - 0.6
Ball bounce 球类反弹	EN 12235	≥90	%	≥90
Technical Characteristics 技术特性				
Abrasion resistance 耐磨性	EN ISO 5470-1	≤1000	mg	≤350
Impact resistance 抗冲击性	EN 1517	≥8	N/m	≥8
Indentation resistance 残余凹陷度	EN 1516	≤0.5	mm	≤0.5
Rolling load resistance 抗滚动承载性	EN 1569	≥ 1500	N	≥1500
	DIN 18032	≥ 1000	N	≥1000
Brightness 反光性	ISO 2813	≤ 30	%	≤30
Surface treatment 表面处理	-	-	-	Triple-Action Protectsol
Surface complex 表面加强处理	-	-	-	D-Max
Foam backing 泡沫背层	-	-	-	CXP
Anti-bacterial and fungicidal treatment 抗菌防霉处理	-	-	-	Sanosol
Classification 类别				

Fire rating 防火等级	EN 13501-1	-	-	Cf1-s1
Color number 颜色数量				8
CE Marking 标识				
	EN 14904:2006	EN ISO 5470-1	EN 13 501-1	EN 13 036- 4