

**DESCRIPTION 规格**

Total thickness 总厚度	EN 428	mm	2
Weight 重量	EN 430	g/m <sup>2</sup>	2950
Width of sheet 卷宽	EN 426	cm	200
Length of sheet 卷长	EN 426	lm	20






**CLASSIFICATION 类别**

Norm / Product specification 产品规范	-	-	EN 649
European classification 欧洲标准	EN 685	class	34 - 43
K rating K级	-	class	K5
Fire rating 防火等级	EN 13 501-1	class	Bfl-s1
Toxic testing 国家建材测试	GB 18586-2001	-	有害物质含量合格
Static electrical propensity 抗静电性	EN 1815	KV	<2
Electrical resistance 抗电阻性	EN 1081	Ω	≥10 <sup>9</sup>
Slip resistance dry 防干滑性	EN 13893	-	≥0.3
Slip resistance wet 防湿滑性	DIN 51 130	class	R9

**PERFORMANCE 性能**

Abrasion resistance 耐磨性	EN 660.2	mm <sup>3</sup>	≤4.0
Abrasion group 耐磨等级	EN 649	group	P
Dimensional stability 尺寸稳定性	EN 434	%	≤ 0.4
Residual indentation 残存凹陷性	EN 433	mm	0.03
Thermal conductivity 热传导性	EN 12 524	W/(m.K)	0.25
Colour fastness 颜色稳定性	EN 20 105 - B02	degree	≥ 6
Chemical products resistance 抗化学性	EN 423	-	OK
Anti-bacterial and fungicidal 抗菌防霉性能	-	-	OK
Special maintenance treatment 特殊维护处理	-	-	PUR
Color number 颜色数量	-	-	26

**CE MARKING 标识**

	EN 14041	 抗静电  Bfl-s1 防火  供地下暖气设备使用  DS 防滑
---	----------	--