

DESCRIPTION 规格

Total thickness 总厚度	EN 428	mm	2.2
Weight 重量	EN 430	g/m ²	2200
Width of sheet 卷宽	EN 426	cm	200
Length of sheet 卷长	EN 426	lm	20







CLASSIFICATION 类别

Norm / Product specification 产品规范	-	-	EN 649
European classification 欧洲标准	EN 685	class	34 - 43
Fire rating 防火等级	EN 13 501-1	class	Cfl-s1
	GB 8624-1997	-	GB 8624 Bf1
Toxic testing 国家建材测试	GB 18586-2001	-	有害物质含量合格
Slip resistance wet 防湿滑性 (赤脚)	DIN51 097	-	AB

PERFORMANCE 性能

Abrasion resistance 耐磨性能	EN 660.2	mm ³	≤ 2.0
Abrasion group 耐磨等级	EN 649	group	T
Dimensional stability 尺寸稳定性	EN 434	%	≤ 0.40
Residual indentation 残存凹陷度	EN 433	mm	≤ 0.10
Thermal conductivity 热传导性	EN 12 524	W/(m.K)	0.25
Colour fastness 颜色稳定性	EN 20 105 - B02	degree	≥ 6
Chemical products resistance 抗化学性	EN 423	-	OK
Anti-bacterial and fungicidal treatment 抗菌防霉处理	-	-	Sanosol
Special maintenance treatment 特殊维护处理	-	-	-
Color number 颜色数量	-	-	7

CE MARKING 标识

	EN 14041	 抗静电	 防火	 供地下暖气设备使用	 防滑	
--	----------	--	--	---	--	---