

DESCRIPTION 规格			
Total thickness 总厚度	ISO 24346 (EN 428)	mm	1.50
Wearlayer thickness 耐磨层厚度	ISO 24340 (EN 429)	mm	0.65
Weight 重量	ISO 23997 (EN 430)	g/m ²	2600
Width of sheet 卷宽	ISO 24341 (EN 426)	cm	200
Length of sheet 卷长	ISO 24341 (EN 426)	lm	21
CLASSIFICATION 类别			
Norm / Product specification 产品规范	-	-	EN 15 102
Fire rating 防火等级	EN 13 501 - 1	class	B-s2,d0
PERFORMANCES 性能			
Colour fastness 颜色稳定性	ISO 105 - B02	degree	≥ 6
Chemical products resistance 抗化学性	ISO 26987 (EN 423)	-	OK
Special maintenance treatment 特殊维护处理	-	-	Protecsol [®]
Anti-bacterial activity 抑菌性能 (E.coli - S.aureus - MRSA 大肠杆菌和金黄色葡萄球菌) ⁽¹⁾	ISO 22196	-	> 99 % inhibits growth 抑菌率
CE MARKING 标识			
	EN 15 102		OK

⁽¹⁾ The implementation of an effective cleaning regime is the most important defence against infections. 实施有效的清洁方法是防止感染最重要的防御措施