

**DESCRIPTION 规格**

Total thickness 总厚度	ISO 24346 (EN 428)	mm	2
Width of sheet 卷宽	ISO 24341 (EN 426)	cm	200
Length of sheet 卷长	ISO 24341 (EN 426)	lm	20
Tile size 片材尺寸	ISO 24342 (EN 427)	mm	608x608
Number of tiles per package 片装数量 / 每箱	-	-	20

**CLASSIFICATION 类别**

Norm / Product specification 产品规范	-	-	ISO 10581(EN 649)
European classification 产品分级	ISO 10874 (EN 685)	class	34 - 43
Fire rating 防火等级	EN 13 501-1	class	Bfl-s1
	GB 8624 - 2012	-	B <sub>1</sub> (B-s1,t0)
Toxic testing 有毒有害物质检测	GB 18586-2001	-	合格
Static electrical propensity 抗静电性	EN 1815	KV	<2
Electrical resistance 抗电阻性	EN 1081	Ω	10 <sup>9</sup> -10 <sup>10</sup>
Slip resistance dry 防干滑性	EN 13893	-	≥0.3
Slip resistance wet 防湿滑性	DIN 51130	class	R9






**PERFORMANCES 性能**

Type binder content 粘合物分级	ISO 10581	type	I
Dimensional stability 尺寸稳定性	ISO 23999 (EN 434)	%	卷材 ≤ 0.4
			片材 ≤ 0.25
Castor chair test 椅子脚轮测试	ISO 4918 (EN 425)	-	OK
Thermal conductivity 热传导性	ISO 10456 (EN 12524)	W/(m.K)	0.25
Colour fastness 颜色稳定性	ISO 105 - B02	degree	≥ 6
Chemical products resistance 抗化学性	ISO 26987 (EN 423)	-	OK
Special maintenance treatment 特殊维护处理	-	-	Evercare
Anti-bacterial activity (E. coli - S. aureus - MRSA) (1) 抗菌性能	ISO 22196		抑菌率>99%
Antiviral activity (human coronavirus 229E) 抗病毒活性 (人类冠状病毒229E)	ISO 21702		99.7% (2小时)
Color number 颜色数量	-	-	33

**ENVIRONMENT / INDOOR AIR QUALITY 环保 / 室内空气质量**

TVOC after 28 days 28天后TVOC (2) 排放量	ISO 16000 - 6	μg/m <sup>3</sup>	<10
Certification 证书	-	-	Floorscore®

**CE MARKING 标识**

	EN 14041	 抗静电  Bfl-s1 防火  供地下暖气设备使用  DS 防滑
---	----------	--

(1) The implementation of an effective cleaning regime is the most important defence against infections. 实施有效的清洁方法是抗感染最重要的防御措施。

(2) TVOC:挥发性有机化合物总排放量