

DESCRIPTION 规格

Total thickness 总厚度	ISO 24346 (EN 428)	mm	4.6
Wearlayer thickness 耐磨层厚度	ISO 24340 (EN 429)	mm	0.7
Weight 重量	ISO 23997 (EN 430)	g/m ²	5595
Tile size 片材尺寸	ISO 24342 (EN 427)	mm	500.5 x 500.5
Number of tiles per package 片装数量/每箱	-	-	10
Coverage / box可铺设面积/每箱	-	sqm	2.5

CLASSIFICATION 类别

Norm / Product specification 产品规范	-	-	EN 652
European classification 产品分级	ISO 10874 (EN 685)	class	34 - 42
Fire rating 防火等级	EN 13501 - 1	class	Bfl-s1
	GB 8624 - 2012	class	B ₁ (B-s1, t0)
Toxic testing 有毒有害物质检测	GB 18586 - 2001	-	合格
Static electrical propensity 抗静电性	EN 1815	kV	< 2
Slip resistance wet 防湿滑性	DIN 51 130	class	R10

PERFORMANCES 性能

Type binder content 粘合物分级	ISO 10582		I
Dimensional stability 尺寸稳定性	ISO 23999 (EN 434)	%	≤ 0.15
Residual indentation 残余凹陷度	ISO 24343-1 (EN 433)	mm	< 0.13
Castor chair test 椅子脚轮测试	ISO 4918 (EN 425)	-	OK
Impact sound insulation 隔音(隔声)性能	ISO 717 - 2	dB	15
Thermal conductivity 热传导性	ISO 10456 (EN 12524)	W/(m.k)	≈ 0.25
Colour fastness 颜色稳定性	ISO 105 - B02	degree	≥ 6
Chemical product resistance 抗化学性	ISO 26987 (EN 423)	-	OK
Special maintenance treatment 特殊维护处理	-	-	Protecso! [®]

ENVIRONMENT / INDOOR AIR QUALITY 环保 / 室内空气质量

TVOC* after 28 days 28天后TVOC*排放量	ISO 16000 - 6	µg/m ³	< 100
Certification 证书	-	-	Floorscore [®]

CE MARKING 标识

	EN 14041	 防滑  供地下暖气设备使用  抗静电  防火
--	----------	--

*TVOC:挥发性有机化合物总排放量